

6,021,770

1

BOW STABILIZER WITH GAME FINDER

This application claims priority from U.S. Provisional Patent Applications Ser. No. 60/053,927 "Bow Stabilizer for Archery" filed on Jul. 28, 1997 and Ser. No. 60/054,172 "Bow Stabilizer Game Finder" filed on Jul. 30, 1997.

TECHNICAL FIELD

The present invention relates to the field of archery. More specifically, it relates to an apparatus for stabilizing the bow, especially when the bow is to be used in hunting, and for tracking the flight of arrows.

BACKGROUND ART

Accuracy in archery can be improved by addition of stabilizing devices to bows to improve the balance and to reduce torque, shock, and vibration otherwise occurring when an arrow is shot. For bows used in hunting, small size, minimal weight, and low noise are distinct additional advantages.

Another aspect of archery as it applies to hunting is the tracking and recovery of arrows and game. Generally, a spool of string is attached to the bow and one end of the string attached to the arrow. As the arrow flies, the string spools out. If the arrow misses the intended target, the string may be followed to retrieve the arrow. If the arrow hits the intended target, the string may be followed to retrieve the game. Simplicity of construction and ease of use are advantages in a string tracker used in hunting.

Various bow stabilizer and tracker structures are known in the background art. U.S. Pat. No. 4,570,608 to Masterfield shows an inertial archery bow stabilizer and vibration dampener having a stud rigidly embedded in the archery bow and an energy-dissipating rod fixed to the stud and projecting forwardly of the stud. The rod is received within an encapsulating sealed cylinder having an internal chamber filled with a viscous fluid in which the rod is disposed. At its outer end, the cylinder is provided with an external stud to which the archer may affix a selected stabilizing weight.

U.S. Pat. No. 4,615,327 to Saunders discloses a two-stage resiliently mounted stabilizer in which the first stage has a first housing resiliently mounted to a pedestal by use of a flat resilient washer and a tubular resilient member within the housing. The second stage of resilient mounting of the stabilizer includes a pair of tubular resilient members, one being disposed in the first housing and the second being disposed in a second housing. A second flat washer separates the two housings and a connecting member is used to connect the second and third tubular members and to tighten them together as well as to tighten the flat washer in a resilient fashion, to allow the second housing to move with respect to the first housing. Additional weights can be attached to the second housing.

U.S. Pat. No. 4,955,356 to Pike et al. discloses an archery bow stabilizer and tracker having first and second threadably connectable body members, the second member being utilized with a removable bushing to allow use of a variety of standard archery tracking cords. An additional weight may be afforded through the use of a threaded extension member.

U.S. Pat. No. 5,016,602 to Mizek discloses a bow stabilizer having a hollow body which defines a chamber, an end plug sealably secured to the hollow body, another end plug sealably secured to an opposite end, and at least one counterweight which is adjustable along a longitudinal axis of the hollow body to balance the archery bow. The chamber of the hollow body is partially filled with granular solids.

2

U.S. Pat. No. 5,273,022 to Leven discloses an apparatus for use with an archery bow stabilizer comprising a resilient elastomeric member, a housing having an open end, means for mounting the elastomeric member in the housing so that an end of the member extends from the housing, means for coupling the apparatus to an archery stabilizer arm at one end, and a stabilizer weight at the opposite end for providing an angularly flexible connection of selected resilience. A weight support arm for an archery bow stabilizer comprises an elongate tubular housing, coupling means for securing the stabilizer to an archery bow, and damping means disposed in the housing in a relaxed position for providing reduction of vibration.

U.S. Pat. No. 5,411,009 to Thompson et al. discloses a compound bow anti-vibration and -noise device having a fluid-filled tube mounted horizontally to the bow body, having a cylinder mounted within the tube, and having a tuning rod or wire mounted within the cylinder.

U.S. Pat. No. 5,535,731 to Webster teaches an archery bow stabilizer that comprises a set of four rods or arms which extend from an attachment block, which block is attachable to a standard stabilizer attachment fitting on an archery bow. The attachment block defines a common intersection for each pair of arms, thereby providing a simple resolution of the forces involved, and provides for each of the four arms to extend into one of the four quadrants defined by the longitudinal and lateral axes of the bow. The outer tip of each of the stabilizing arms or rods is downwardly disposed. The downwardly disposed arms include removably adjustable masses at their tips, which also serve to lower the common center of mass of the bow and stabilizer assembly to a point approximating the hand grip of the bow.

U.S. Pat. No. 5,649,527 to Olsen et al. teaches a combination archery bow stabilizer and string tracker mounting adapter having a telescopic capability to raise or lower the string tracker. The string tracker is mounted to a 360-degree rotatable arm. The adapter and rotatable arm are capable of adjustment for the needs of the individual archer or archery bow to which it is mounted.

U.S. Pat. No. 5,735,257 to Walk shows a multi-chamber stabilizer with an elongate housing having a plurality of separate internal chambers suitable for containing damping material or damping devices, which may be of different types.

DISCLOSURE OF INVENTION

Disclosed herein is a combination bow stabilizer and string tracker device directly mountable to a bow. The device is contained in a single body having a section for holding a spool of tracking string and having a section holding shock absorption and vibration damping material. The stabilizer and string tracker combination is designed to be mounted near the center of the bow and parallel to the general direction of an arrow held in a shooting position. The combination stabilizer combines the functions of stabilizing the bow (especially against torque and vibration) during release of an arrow, and tracking the arrow after release.

The apparatus is formed from a hollow cylinder. A mounting rod is completely embedded in an elastomer, preferably a shock-absorbing and vibration-damping viscoelastic polymer material, contained near one end of the cylinder. The viscoelastic polymer material is preferably a flexible polyurethane of essentially linear structure, containing unsatisfied hydroxyl groups, and having a compression set of less than 15%, an elongation at break of at least 500%, and a

6,021.770

3

recovery after compression which is delayed by at least 0.7 seconds. A suitable viscoelastic polymer material is the material "Sorbothane" available from Sorbothane, Inc. of Kent, Ohio. "Sorbothane" exhibits high stability over a very broad temperature range. Such stability is important for archery during various seasons of the year and in various kinds of weather, as the effect of the stabilizer will remain constant despite environmental temperature variations. The mounting rod is aligned with the longitudinal axis of the body cylinder and has a moderate degree of freedom to move transversely. There is less ability to move longitudinally (toward and away from the bow) as this could adversely effect the balance. There is no direct contact between the mounting rod on the one hand and body cylinder or cap on the other hand. In particular, there is no metal-to-metal contact. The elastomer material thus maintains isolation between the bow and mounting rod and all other parts of the stabilizer and game tracker.

A chamber at the opposite end of the body from the mounting holds a spool of tracking string. A line-retaining cap is threaded into the body. This cap has a double tapered orifice that is smooth with no sharp edges, to allow easy pay out of the tracking line. When the bow is shot, the shock and vibration, including any effect of the line paying out, are absorbed by the "Sorbothane," thus minimizing deflection of the bow at the critical moment of firing.

The weight and moment of inertia of the stabilizer may be changed by the use of materials of various densities for the body and the line-retaining cap so the stabilizer may remain small and compact, be useful for various combinations of bow, arrow, and archer ability, yet still hold a similarly suitable amount of tracking line.

Therefore it is an object of the present invention to provide an extremely quiet stabilizer taking advantage of the special properties of a viscoelastic polymer. It is a further object of the present invention to provide a combination bow stabilizer and game tracker in a single compact body. It is a further object of the present invention to provide a combination bow stabilizer and game tracker having a shock absorption and vibration damping capability over a wide range of temperatures. It is a still further object of the present invention to provide stabilizer and game tracker combination design capable of different inertial characteristics in the same compact size.

BRIEF DESCRIPTION OF DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

FIG. 1 is a side view of a bow showing a bow stabilizer and game finder made in accordance with the present invention attached.

FIG. 2 is a side view of a bow stabilizer and game finder made in accordance with the present invention.

FIG. 3 is an end view from the mounting end of the bow stabilizer and game finder of FIG. 2.

FIG. 4 is an end view from the cap end of the bow stabilizer and game finder of FIG. 2.

FIG. 5 is a cross-sectional side elevation view of the bow stabilizer and game finder of FIG. 2.

FIG. 6 is a cross-sectional view through section 6—6 of FIG. 5.

4

FIG. 7 is a cross-sectional end view through section 7—7 of FIG. 5.

BEST MODE FOR CARRYING OUT THE INVENTION

FIG. 1 shows a bow 10 with bow stabilizer and game tracker 20 attached. Bow stabilizer and game tracker 20 is preferably attached to the handle riser of the bow, below the grip and extending generally forward from the face of the bow as shown in FIG. 1. FIG. 1 is not drawn to scale.

As shown in FIGS. 2, 3, 4, and 5, bow stabilizer and game tracker 20 has a generally cylindrical body 30 having a major longitudinal axis, with a cap end 40 and a mounting end 50 located at opposite ends of the longitudinal axis. Body 30 has an outer surface 60 into which grip grooves 80 have been formed. Grooves 80 allow for gripping bow stabilizer and game tracker 20 when mounting it to bow 10. Line-retaining cap 100, which is detachably mounted to cap end 40 of bow stabilizer and game tracker 20, has a line exit orifice 110 having an outer tapered surface 120 to reduce drag as tracking line 165 exits from line exit orifice 110. Line exit orifice 110 is concentric with the major longitudinal axis of cylindrical body 30. Body 30 and line-retaining cap 100 may be fabricated from steel, copper, brass, aluminum, or plastic, for example. Extending from mounting end 50 of bow stabilizer and game tracker 20 is mounting shaft 200. Shaft 200 is flexibly mounted along the major longitudinal axis of body 30 such that angular deflection in any direction from the longitudinal axis of cylindrical body 30 is permitted. Mounting shaft 200 has hex extension 210 to allow tightening of bow stabilizer and game tracker 20 to bow 10 by first threaded end 220 of mounting shaft 200. Hex extension 210 may be a nut threaded onto mounting shaft 200.

It is important for optimum operation of the stabilizer that there be no direct contact between the mounting shaft 200 on the one hand and body cylinder 30 or cap 40 on the other hand. In particular, there should be no metal-to-metal contact. An elastomer material, described in detail below, maintains vibration isolation between the combination of bow 10 and attached mounting shaft 200 from all other parts of the stabilizer and game tracker.

FIG. 3 is an end view of mounting end 50 of bow stabilizer and game tracker 20. Opening 90 in end 50 of body 30 is sized to allow clearance for angular deflection of mounting shaft 200 from the longitudinal axis of cylindrical body 30. Opening 90 is smaller in diameter than the diameter of inner surface 70 of cylindrical body 30. FIG. 4 is an end view of cap end 40 of bow stabilizer and game tracker 20, showing inner tapered surface 130 of line exit orifice 110 in line-retaining cap 100.

As shown in FIGS. 4, 5 and 6, cylindrical body 30 has threads 75 cut into inner wall 70 at cap end 40 for receiving matching threaded ring 150 of line-retaining cap 100. Cylindrical body 30 also has lip 95 at mounting end 50. Lip 95 may be integral to cylindrical body 30 or may be a press fit ring. Middle portion 240 of mounting shaft 200 extends through first mounting elastomer 260, first retaining washer 270, vibration damping elastomer 280, second mounting elastomer 290 and second retaining washer 300. The assembly of first mounting elastomer 260, first retaining washer 270, vibration damping elastomer 280, second mounting elastomer 290 and second retaining washer 300 is compressed against lip 95 by lock-nut 310 engaging second threaded end 250 of mounting shaft 200. First and second retaining washers 270 and 300 are formed of any elastomer.